

# LS60 Pick and Place Machine



**Brand:** DDM Novastar

**Product Code:** 013803049541

**Availability:** In Stock

**Weight:** 0.00kg

**Dimensions:** 1,016.00mm x 1,321.00mm x 1,346.20mm

## Short Description

Most flexible premium model with unmatched precision for low to medium production.

## Description

The most flexible pick and place system, the LS60, offers technologically advanced features with a 13" x 32" (330 mm x 813 mm) work area, 96 single feeder positions (up to 144 feeders using bank feeders) where quick setup, ease of operation and high reliability are paramount.

- The highest quality with the most advanced technology at a cost effective solution
- Accuracy +/- .001" (0.025 mm)
- Placement rates up to 4800 cph
- The best GUI (graphical user interface) in its class using Windows based software allows programming in minutes
- Up to 96 tape feeders, 144 tape positions with bank feeders
- Accurately places a wide range of components including 0201s, LED's, BGAs, 15mil pitch QFPs, SMT Connectors and many others\*
- Servo driven, position feedback from a 2 micron linear scale coupled with a precision placement head
- Integrated system with on-the-fly component centering using Mechanical fingers (Standard) or Laser Technology (Cyber-optics®) (Optional)
- Cut tape, loose, tube, or tray feeders

## Specification

Pick and Place Machines	
Dispenser Option	Up to 10,000 dots/hour
Fine Pitch Capability	To 15 mil pitch (0.381 mm)
Largest Component Size	1.378" (35 mm) square body
Laser Centering	Touch-less Cyber-optics® laser (OPTION ONLY)
Matrix Tray Feeders	With Board/Matrix tray holders
Max Board Size	13.5" x 32" (343 mm x 813 mm)
Max No. of Feeders (8 mm Tape)	96
Max No. of Feeders with L-GB-12 Bank Feeders	144
Max Placement Rate	4800 cph
Max Travel Area	22" (X axis) x 32" (Y axis) (560 mm x 813 mm)
Overall Dimensions	40" x 52" x 53" (1016 mm x 1321 mm x 1346.2 mm)
Placement Accuracy	± 0.001" (0.025 mm)
Smallest Component Capability	0201 components
Tape Feeders	8, 12, 16, 24, 32, 44 mm (electrical)
Typical Verifiable Placement Rate	2500-3600 cph
Vibratory Feeders	Loose, tube, stick (frequency & amplitude control)
Vision System	Color CCD Card Camera