

24FS Single and 24FD Dual Wave Solder Machines



Brand: DDM Novastar
Product Code: 013803049541
Availability: In Stock
Weight: 0.00kg
Dimensions: 0.00mm x 0.00mm x 0.00mm

Short Description

Cost effective, medium to high volume, automatic titanium finger 24" single and dual wave soldering systems

Description

Automatic wave solder system with self-contained fluxing, preheating and laminar (smooth) solder wave modules.

- Automatic wave solder system
- Best value through cutting-edge technology
- Ready-to-go fluxing, preheating and wave modules
- Quick ROI (Return on Investment)
- Exceptional accuracy and repeatability
- Lead or Lead-Free solder compatibility
- Easy to use
- Low maintenance
- Titanium Finger Conveying System
- Single (24FS) and dual (24FD) wave capability

Specification

Wave Solder	
Approx Warm-up Time	150 minutes

Compressed Air	10 CFM @ 60 PSI (17 m ³ /hr @ 4 bar)
Foam Fluxer Tank	2 gal (8 litre)
Max Conveyor Speed	8 ft/min (2.5 m/min)
Max Preheat 1 Temp	356°F (180°C)
Max Preheat 3 Temp	428°F (220°C)
Max Wave Height	0-3/8" / 0-10 mm
Preheat 1 Power	4.8 kW
Preheat 2 Power	N/A
Preheat 3 Power	2.0 kW
Solder Pot Capacity	1325 lbs (600 kg)
Solder Pot Power	9.5 kW
Wave Width	24" (600 mm)